



LED Bulb mini globe 25w

T100 / E27

Features

- High luminous efficacy and reliability
- 4 years guarantee
- Life Time 25,000 Hrs
- No Flicker, No UV Radiation.
- Reduced replacement and maintenance costs.



Technical Data

Electrical Data

| | |
|----------------------|----------|
| Nominal wattage (W) | 25W |
| Nominal Voltage | 220-240V |
| Nominal Current (mA) | 125 mA |
| Frequency (Hz) | 50/60 Hz |
| Power Factor | 0.9 |

Photometrical Data

| | |
|-------------------------------------|---------------|
| Nominal luminous flux (lumen) | 2500 lm |
| Luminous efficacy | 100 lm/w |
| Color temperature | 6500 K |
| Light color | Cool Daylight |
| Color rendering index | ≥80 |
| Beam angle | 270° |
| Standard Division of color matching | ≤6 sdc |




➤ Color Temperature

Cool daylight
6500 K



➤ Dimensions & Weight

| | | |
|-------------|------------|---|
| Size (D*H) | Ø98*198 mm |  |
| Weight (gm) | 160 gm | |

➤ Application & Mounting

| | |
|---------------------------|----------------|
| Ambient temperature range | -10°C to +40°C |
| Product color | White |
| Type of protection | IP20 |
| Dimmable | No |
| Application environment | Indoor |

➤ Certificates & Standards

| | |
|-----------|-----------|
| Standards | CE / RoHS |
|-----------|-----------|

➤ Logistical Data

| Type | Product Code | No. Packaging | Packaging Unit Code |
|---------|--------------|---------------|---------------------|
| 25W Day | 909010902560 | 1/24 PCS | 24909010902560 |