

LED Downlight 24w

Recessed



Features

- High luminous efficacy and reliability
- 4 years guarantee
- Life Time 25,000 Hrs
- No Flicker, No UV Radiation.
- Reduced replacement and maintenance costs.


Technical Data

Electrical Data


| | |
|----------------------|----------|
| Nominal wattage (W) | 24W |
| Nominal Voltage | 220-240V |
| Nominal Current (mA) | 195 mA |
| Frequency (Hz) | 50/60 Hz |
| Power Factor | 0.5 |

Photometrical Data


| | |
|-------------------------------------|----------------------------|
| Nominal luminous flux (lumen) | 2160 lm |
| Luminous efficacy | 90lm/w |
| Color temperature | 3000 K / 6500 K |
| Light color | Warm White / Cool Daylight |
| Color rendering index | ≥80 |
| Beam angle | 110° |
| Standard Division of color matching | ≤6 sdcM |



24W Day



24W Warm



➤ Color Temperature

Cool daylight
6500 K



warm white
3000 K

➤ Dimensions & Weight

| | | |
|-------------|-------------|--|
| Size (D*H) | ∅ 215*38 mm | |
| Cutout Hole | ∅ 200 mm | |
| Weight (gm) | 250 gm | |

➤ Application & Mounting

| | |
|---------------------------|----------------|
| Ambient temperature range | -10°C to +40°C |
| Product color | White |
| Type of protection | IP20 |
| Dimmable | No |
| Application environment | Indoor |

➤ Certificates & Standards

| | |
|-----------|-----------|
| Standards | CE / RoHS |
|-----------|-----------|

➤ Logistical Data

| Type | Product Code | No. Packaging | Packaging Unit Code |
|----------------|--------------|---------------|---------------------|
| 24w Round warm | 905020502431 | 1/24 PCS | 24905020502431 |
| 24w Round Day | 905020502461 | 1/24 PCS | 24905020502461 |