

LED Floodlight 100w



Features

- High luminous efficacy and reliability
- 5 years guarantee
- Life Time 50,000 Hrs
- No Flicker, No UV Radiation.
- Reduced replacement and maintenance costs.



Technical Data

Electrical Data

Nominal wattage (W)	100W
Nominal Voltage	220-240V
Nominal Current (mA)	505 mA
Frequency (Hz)	50/60 Hz
Power Factor	0.9

Photometrical Data

Nominal luminous flux (lumen)	10000 lm
Luminous efficacy	100lm/w
Color temperature	6500 K
Light color	Cool Daylight
Color rendering index	≥80
Beam angle	110°
Standard Division of color matching	≤5 sdcn



➤ Color Temperature

Cool daylight
6500 K



➤ Dimensions & Weight

Size (L*B*H)	300*260*92 mm	
Weight (gm)	1875 gm	

➤ Application & Mounting

Ambient temperature range	-20°C to +50°C
Product color	Grey
Type of protection	IP65
Dimmable	No
Application environment	Outdoor

➤ Certificates & Standards

Standards	CE / RoHS
-----------	-----------

➤ Logistical Data

Type	Product Code	Inner box Dimensions	No. Packaging	Gross Weight
100W	909060810065	312*273*100 mm	1 PCS	2050 gm