

# LED Floodlight 50w



## Features

- High luminous efficacy and reliability
- 5 years guarantee
- Life Time 50,000 Hrs
- No Flicker, No UV Radiation.
- Reduced replacement and maintenance costs.


## Technical Data

### Electrical Data


Nominal wattage (W)	50W
Nominal Voltage	220-240V
Nominal Current (mA)	252 mA
Frequency (Hz)	50/60 Hz
Power Factor	0.9

### Photometrical Data

Nominal luminous flux (lumen)	5000 lm
Luminous efficacy	100lm/w
Color temperature	6500 K
Light color	Cool Daylight
Color rendering index	≥80
Beam angle	110°
Standard Division of color matching	≤5 sdcn



50W Cool daylight



## ➤ Color Temperature

Cool daylight  
6500 K



## ➤ Dimensions & Weight

Size (L*B*H)	215*225*53 mm	
Weight (gm)	815 gm	

## ➤ Application & Mounting

Ambient temperature range	-20°C to +50°C
Product color	Grey
Type of protection	IP65
Dimmable	No
Application environment	Outdoor

## ➤ Certificates & Standards

Standards	CE / RoHS
-----------	-----------

## ➤ Logistical Data

Type	Product Code	Inner box Dimensions	No. Packaging	Gross Weight
50W	909060805065	220*285*65 mm	1 PCS	990 gm