

LED STRIP

SMD LED 2835 Roll100M 180L/M

13W/M



Features

- High luminous efficacy and reliability
- 3 years guarantee
- Life Time 30,000 Hrs
- No Flicker, No UV Radiation.
- Reduced replacement and maintenance costs.

Technical Data


Electrical Data

| | |
|----------------------|----------|
| Nominal wattage | 13W/M |
| Nominal Voltage | 220-240V |
| Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| Power Supply current | 8A |


Photometrical Data

| | |
|-------------------------------------|--|
| Nominal luminous flux | 1350 lm/M +/-5% |
| Luminous efficacy | 104 lm/w |
| Color temperature | 3000 K/4000 k / 6500 K |
| Light color | Warm White/ Cool White / Cool Daylight |
| Color rendering index | ≥80 |
| Standard Division of color matching | ≤3 sdcM |


Day



Warm



cool



➤ Color Temperature

Cool daylight
6500 K




Warm white
3000 K

Cool white
4000 K

➤ Dimensions & Weight

Size (L*D) 100 M * 2cm

Weight (gm) 8.5Kg



1 Roll 100M 180L/M

➤ Specification

| | |
|----------------------------|----------------|
| Ambient temperature range | -10°C to +40°C |
| LED Strip cutting distance | 20 Cm |
| Type of protection | IP65 |
| Dimmable | No |

➤ Certificates & Standards

| | |
|-----------|-----------|
| Standards | CE / RoHS |
|-----------|-----------|

➤ Logistical Data

| Type | Product Code | No. Packaging |
|------|---------------|---------------|
| Day | 6223014080651 | 1 Roll |
| Cool | 6223014080644 | 1 Roll |
| Warm | 6223014080637 | 1 Roll |